



AQUATEK®



SUPER CONCENTRATE

Eliminates water & prevents microbial growth in petroleum hydrocarbons such as crude oil, lubricating oil, diesel fuel and heating oil.

When to use:

- ▶ When storing fuel in tanks or storing equipment.
- ▶ When humidity or condensation levels are high.

What it does:

- ▶ Prevents water from accumulating.
- ▶ Safely removes water from condensation.

How much to add:

32 oz. will treat up to 2,980L / 655 imp. gal. / 786 US gal.

For extreme conditions increase dosage.

NOTE: AquaTek is not meant to dispense large amounts of water. If you have large accumulations, contact DSG for assistance.

* Certified compliant for use in Low Emission Engines & ULSD fuel.

* EPA Registered.

SIZE	TREATS	SKU	AMOUNT
32 oz.	2,980 L / 786 US gal.	AT32	12 x 32 oz.

DBFUELTREAT&ECON_1211

1-800-667-6879 230 - 29th Street East, Saskatoon, SK S7L 6Y6



POWER SYSTEMS
ENGINES ■ GENERATORS ■ FUEL SCIENCE ■ PARTS & SERVICE



The parties agree that the implied warranties that are set out in the Sale of Goods Act, are excluded and shall not apply to goods sold or services supplied. The parties also agree that only the warranty expressly provided by DSG Power Systems or Saskatoon Diesel Services Ltd. shall apply to the goods sold or services provided. The purchaser or his agent by entering into this transaction acknowledges that he/she has read this agreement and warranty disclaimers herein and also acknowledges that this agreement comprised the entire agreement between the parties and that there are no antecedent or extrinsic representation or collateral agreements that terms are strictly net 30 days. Warranty is set out in the terms and conditions of sale above. Warranty is limited to the original purchaser. 1-800-667-6879. If you encounter any trouble call this number. Failure to do so will null and void all warranties.