



POLAR MAX®



SUPER CONCENTRATE

Cold Weather Preventative Diesel Fuel Anti-Gel Additive

Use Summer Fuel in the Winter and Save!!

Recommended for use prior to winter storage of machinery, to prevent spring start-up problems.

When to use:

- ▶ Temperature drops below 0° C.
- ▶ You are using fuel meant for warmer temperatures.
- ▶ You store equipment during cold winter months.
- ▶ You need a cost-effective cold flow improver.

What it does:

- ▶ Prevents fuel from gelling as low as -45° C.
- ▶ Stops water condensation as low as -54° C.
- ▶ Depresses pour-point. Lowers cold filter plug-point.

* Certified compliant for use in Low Emission Engines & ULSD fuel.

*EPA Registered.

Available In - 32 oz.

Bulk Sizes Available - Please Call to Inquire

SKU: PM32



Temp.	32 oz. TREATS	SKU	AMOUNT
0°C to -18°C	1820 L / 480 US gal.	PM32	12 x 32 oz.
-19°C to -39°C	910 L / 240 US gal.	PM32	12 x 32 oz.
-40°C to -60°C	455 L / 120 US gal.	PM32	12 x 32 oz.

Meets & exceeds industry standards:

- CFPP (ASTM D6371)
- EMA/TMC Criteria for Lubricity
- Lubricity (ASTM D6079)
- Water Tolerance (ASTM D1094)

DBFUELTREAT&ECON_1211

1-800-667-6879 230 - 29th Street East, Saskatoon, SK S7L 6Y6



The parties agree that the implied warranties that are set out in the Sale of Goods Act, are excluded and shall not apply to goods sold or services supplied. The parties also agree that only the warranty expressly provided by DSG Power Systems or Saskatoon Diesel Services Ltd. shall apply to the goods sold or services provided. The purchaser or his agent by entering into this transaction acknowledges that he/she has read this agreement and warranty disclaimers herein and also acknowledges that this agreement comprised the entire agreement between the parties and that there are no antecedent or extrinsic representation or collateral agreements that terms are strictly net 30 days. Warranty is set out in the terms and conditions of sale above. Warranty is limited to the original purchaser. 1-800-667-6879. If you encounter any trouble call this number. Failure to do so will null and void all warranties.